




**PARTIAL RECESSED**



**2-way tiltable COB led downlight (Partial recessed)**

Product picture	Item no.	LED Brand	Power	CRI>	CCT	Lamp Lumen	Voltage (AC)	Beam angle	Glass	Color of Body	Dimension (mm)	Qty & G.W. / CTN	CTN size (CM) & V.W.	Dim Types	Driver (no flicker)	MOQ (PC)
																1 CTN
	A00433000	SGLED CREE CITIZEN	7W	90	2700K 3000K 4000K 6000K	600-950lm	220-240V	25° 38° 55° 110°	clear	white black	ø 96*H40 ø 75-85 (cutting)	48pcs 26kg	45x45x38 15.5kg	Not-dim Triac 1-10V Dali	Lifud Eaglerise Easeic Easeic	48
	A00433001	SGLED CREE CITIZEN	12W	90	3000K 4000K 6000K	1100-1500lm	220-240V	20° 38° 60° 110°	clear	white black	ø 120*H40 ø 95-110 (cutting)	36pcs 26kg	53x41x41 18kg	Not-dim Triac 1-10V Dali	Lifud Eaglerise Easeic Easeic	36
	A00433002	SGLED CREE CITIZEN	20W	90	3000K 4000K 6000K	1600-2500lm	220-240V	15° 38° 60° 110°	clear	white black	ø 150*H40 ø 125-140 (cutting)	18pcs 21kg	51x51x35 18.5kg	Not-dim Triac 1-10V Dali	Lifud Eaglerise Easeic Easeic	18
	A00433003	SGLED CREE CITIZEN	30W	90	3000K 4000K 6000K	2900-3600lm	220-240V	20° 38° 60° 110°	clear	white black	ø 180*H40 ø 145-170 (cutting)	16pcs 25kg	41x78x34 22kg	Not-dim Triac 1-10V Dali	Lifud Eaglerise Easeic Easeic	16



**Fixed COB led downlight (Partial recessed)**

Product picture	Item no.	LED Brand	LED Consumption	CRI>	CCT	Lamp Lumen	Voltage (AC)	Beam angle	UGR	Color of Body	Dimension (mm)	Qty & G.W. / CTN	CTN size (CM) & V.W.	Dim Types	Driver brand	MOQ (PC)
																1 CTN
	A00433004	SGLED CREE CITIZEN	7W	90	2700K 3000K 4000K 6000K	600-950lm	220-240V	20° 38° 55° 110°	19	white black	ø 96*H40 ø 75-85 (cutting)	48pcs 26kg	45x45x38 15.5kg	Not-dim Triac 1-10V Dali	Lifud Eaglerise Easeic Easeic	48
	A00433005	SGLED CREE CITIZEN	12W	90	3000K 4000K 6000K	1100-1500lm	220-240V	20° 38° 60° 110°	19	white black	ø 120*H40 ø 95-110 (cutting)	36pcs 26kg	53x41x41 18kg	Not-dim Triac 1-10V Dali	Lifud Eaglerise Easeic Easeic	36
	A00433006	SGLED CREE CITIZEN	20W	90	3000K 4000K 6000K	1600-2500lm	220-240V	15° 38° 60° 110°	19	white black	ø 150*H40 ø 125-140 (cutting)	18pcs 21kg	51x51x35 18.5kg	Not-dim Triac 1-10V Dali	Lifud Eaglerise Easeic Easeic	18
	A00433007	SGLED CREE CITIZEN	30W	90	3000K 4000K 6000K	2900-3600lm	220-240V	15° 38° 60° 110°	19	white black	ø 180*H40 ø 145-170 (cutting)	16pcs 25kg	41x78x34 22kg	Not-dim Triac 1-10V Dali	Lifud Eaglerise Easeic Easeic	16





**PARTIAL RECESSED**

**Fixed anti-glare COB led downlight (Partial recessed)**

Product picture	Item no.	LED Brand	LED Consumption	CRI>	CCT	Lamp Lumen	Voltage (AC)	Beam angle	UGR	Color of Body	Dimension (mm)	Qty & G.W. / CTN	CTN size (CM)	Dim Types	Driver brand	MOQ (PC)
																1 CTN
	A00433008	SGLED CREE CITIZEN	7W	90	2700K 3000K 4000K 6000K	500-800lm	220-240V	25° 38° 50° 90°	17	white black	∅ 96*H40	48pcs 26kg	45x45x38 15.5kg	Not-dim	Lifud	48
											∅ 75-85 (cutting)			Triac	Eaglerise	
														1-10V	Easeic	
														Dali	Easeic	
	A00433009	SGLED CREE CITIZEN	12W	90	3000K 4000K 6000K	1000-1400lm	220-240V	25° 38° 50° 90°	17	white black	∅ 120*H40	36pcs 26kg	53x41x41 18kg	Not-dim	Lifud	36
											∅ 95-110 (cutting)			Triac	Eaglerise	
														1-10V	Easeic	
														Dali	Easeic	
	A00433010	SGLED CREE CITIZEN	20W	90	3000K 4000K 6000K	1500-2400lm	220-240V	15° 38° 55° 90°	17	white black	∅ 150*H40	18pcs 21kg	51x51x35 18.5kg	Not-dim	Lifud	18
											∅ 125-140 (cutting)			Triac	Eaglerise	
														1-10V	Easeic	
														Dali	Easeic	
	A00433011	SGLED CREE CITIZEN	30W	90	3000K 4000K 6000K	2700-2500lm	220-240V	20° 38° 55° 90°	17	white black	∅ 180*H40	16pcs 25kg	41x78x34 22kg	Not-dim	Lifud	16
											∅ 145-170 (cutting)			Triac	Eaglerise	
														1-10V	Easeic	
														Dali	Easeic	

Remarks: 1. Standard optical anti-glare shield is shiny silver & white; Optional color: Champagne, gold, matt silver, black ( shiny / matt ) , MOQ 200pcs.






**PARTIAL RECESSED**

**2-way tiltable super anti-glare COB led downlight (Partial recessed)**

Product picture	Item no.	LED Brand	LED Consumption	CRI>	CCT	Lamp Lumen	Voltage (AC)	Beam angle	UGR	Color of Body	Dimension (mm)	Qty & G.W. / CTN	CTN size (CM)	Dim Types	Driver brand	MOQ (PC)
																1 CTN
	A0043301 2	SGLED CREE CITIZEN	7W	90	2700K 3000K 4000K 6000K	300-400lm	220-240V	20°	10-13	white black	∅ 96*H40	48pcs 26kg	45x45x38 15.5kg	Not-dim	Lifud	48
											Triac			Eaglerise		
											1-10V			Easeic		
											Dali			Easeic		
	A0043301 3	SGLED CREE CITIZEN	12W	90	3000K 4000K 6000K	600-800lm	220-240V	15°	10-13	white black	∅ 120*H40	36pcs 26kg	53x41x41 18kg	Not-dim	Lifud	36
											Triac			Eaglerise		
											1-10V			Easeic		
											Dali			Easeic		
	A0043301 4	SGLED CREE CITIZEN	20W	90	3000K 4000K 6000K	900-1400lm	220-240V	15°	10-13	white black	∅ 150*H40	18pcs 21kg	51x51x35 18.5kg	Not-dim	Lifud	18
											Triac			Eaglerise		
											1-10V			Easeic		
											Dali			Easeic		
	A0043301 5	SGLED CREE CITIZEN	30W	90	3000K 4000K 6000K	1600-2000lm	220-240V	15°	10-13	white black	∅ 180*H40	16pcs 25kg	41x78x34 22kg	Not-dim	Lifud	16
											Triac			Eaglerise		
											1-10V			Easeic		
											Dali			Easeic		



**Attention :**

1. Standard IP rate is IP33.
2. Special CCT / CRI (SGLED LED only) must meet our MOQ (≥200pcs), or there will be extra sample fee.
3. 110V versions adopted UL/ETL certified driver, no-dim 12-40W +
4. EXW price (FOB SZ)
5. Warranty: 2 years
6. Lead time: 7-10 working days.
7. Payment term: TT in advance